

WASHDOWN SCALE



HL-WP SERIES



Sealed case locks out water and dust

The HLWP Series of compact digital scales can be completely submerged in water. This allows for easy cleaning and eliminates the concern over accidental exposure to wet environments. The HLWP was designed to withstand the variety of harsh conditions found in commercial and industrial facilities.

Features

- IP67/NEMA-4X
- Stainless Steel Construction
- Small footprint
- Portable
(6AA batteries not included)
- Clear LCD display
- Stability indicator
- Tare function
- Auto power off
- AC adapter (optional)
- Multiple Units

Options (order separately)

- FV-05 AC adapter 110VAC
- FV-06 AC adapter 220VAC
(AC adapters are not waterproof)



HL-WP Small Pan
128 mm / 5" sq.



HL-WP Large Pan
170 mm / 6.8" wide
137 mm / 5.4" deep

HL-WP Series Specifications

MODEL	HL-300WP	HL-1000WP	HL-3000WP	HL-3000WPN*	HL-3000LWP	HL-3000LWPN*
Pounds (lb)	—	2.2 x 0.001 lb	6.6 x 0.002 lb	6.6 x 0.002 lb	6.6 x 0.002 lb	6.6 x 0.002 lb
Pounds/Ounces (lb/oz)	—	2 lb, 3.3 oz x 0.1 oz	6 lb, 9.8 oz x 0.1 oz	—	6 lb, 9.8 oz x 0.1 oz	—
Ounces (oz)	10.58 x 0.01 oz	35.28 x 0.02 oz	105.8 x 0.1 oz	105.8 x 0.1 oz	105.8 x 0.1 oz	105.8 x 0.1 oz
Grams (g)	300 x 0.1 g	1000 x 0.5 g	3000 x 1 g	3000 x 1 g	3000 x 1 g	3000 x 1 g
Platform Size	128 mm / 5" square				170 x 137 mm / 6.8 x 5.4" (w x d)	
Linearity	0.1 g	0.5 g	1 g			
Repeatability	0.1 g	0.5 g	1 g			
Std. Deviation						
Display	12 mm / 0.5 inch, 7 segment LCD					
Power	6 'AA' size batteries (not included) or FV-05 AC adapter (option)					
Battery Life	Approx. 100 hours (manganese type), 200 hours (alkaline at 20°C / 68°F)					
Operating Temp	-10°C - 40°C (35°C for NTEP) / 14°F - 104°F (95% for NTEP) RH less than 85%					
Weight	Approx. 870 g / 2 lb					

* NTEP (Legal For Trade)

Specifications are subject to change for without notice.

Selectable Weighing Modes:



gram mode



lb mode



oz mode



lb/oz mode



1756 Automation Parkway
San Jose, CA 95131
(800) 726-3364 or (408) 263-5333
Email: scales@andweighing.com
www.andweighing.com

